



## TOGGLE SWITCHES

### VERTICAL MOUNTING "V3"

Part Number
C&K7101MD9V3BE
C&K7103MD9V3BE
C&K7105MD9V3BE
C&K7107MD9V3BE

SPDT

H=11.68  
W=8.13  
D=15.75  
Bush L=7.11  
Toggle L=6.86



Part Number
C&K7201MD9V3BE
C&K7203MD9V3BE
C&K7205MD9V3BE
C&K7207MD9V3BE



H=11.68  
W=8.13  
D=15.75  
Bush L=7.11  
Toggle L=6.86

DPDT

### Explanation of Part Numbers:

Example - 7101MD9ABE

- 7101 - Switch function
- M - Actuator Standard
- D9 - Non Threaded Bushing
- A - Right Angle Pins
- B - Contact Material - Gold
- E - Epoxy Seal






Quality switches from the USA

- Also available in many other options.
- Actuators
  - Terminations
  - Bushings
  - Vertical & Horizontal Mounting

### RIGHT ANGLE MOUNTING "A"


Part Number
C&K7101MD9ABE
C&K7103MD9ABE
C&K7105MD9ABE
C&K7107MD9ABE

SPDT



Part Number
C&K7201MD9ABE
C&K7203MD9ABE
C&K7205MD9ABE
C&K7207MD9ABE




DPDT



### RIGHT ANGLE MOUNTING "AV2"

Part Number
C&K7101MD9AV2BE
C&K7103MD9AV2BE
C&K7105MD9AV2BE
C&K7107MD9AV2BE

SPDT



Part Number
C&K7201MD9AV2BE
C&K7203MD9AV2BE
C&K7205MD9AV2BE
C&K7207MD9AV2BE

DPDT



## TINY TOGGLE SWITCHES

### T SERIES

- \* Gold plated contacts allow low level switching.
- \* Epoxy sealed terminations
- \* Threaded bush type for panel mount
- \* Also available with no thread

- Contact Rating: 2Amps @ 120VAC or 28VDC  
 Electrical Life: 60,000 cycles at full load  
 Contact Resistance: 20m $\Omega$  initial @ 2 - 4VDC 100mA  
 Insulation Resistance: 1,000M $\Omega$  min  
 Dielectric Strength: 1,000VRMS min  
 Operating Temperature: -30°C to 85°C

Also available in many other options.

- Actuators
- Bushings
- Terminations
- Vertical Mounting
- Horizontal mounting

NO. POLES	MODEL NO.	SWITCH FUNCTION			MOM. = Momentary	SCHEMATICS
		POS. 1	POS. 2	POS. 3		
SPDT	C&K7101SHZQE	ON	NONE	ON		
	C&K7103SHZQE	ON	OFF	ON		
	C&K7105SHZQE	MOM.	OFF	MOM.		
	C&K7107SHZQE	ON	OFF	MOM.		
	C&K7108SHZQE	ON	NONE	MOM.		
DPDT	C&K7201SHZQE	ON	NONE	ON		
	C&K7203SHZQE	ON	OFF	ON		
	C&K7205SHZQE	MOM.	OFF	MOM.		
	C&K7207SHZQE	ON	OFF	MOM.		
	C&K7208SHZQE	ON	NONE	MOM.		

## MINIATURE SEALED TOGGLE SWITCHES

### E SERIES

- \* Gold plated contacts allow low level switching.
- \* Epoxy sealed terminations
- \* Processed sealed to withstand machine soldering and pressure wash cleaning.

- Contact Rating: 0.4VA max. @ 20VAC or DC max  
 Electrical Life: 40,000 cycles at full load  
 Contact Resistance: 10m $\Omega$  initial @ 2 - 4VDC 100mA  
 Insulation Resistance: 1,000M $\Omega$  min  
 Dielectric Strength: 1,000VRMS min  
 Operating Temperature: -30°C to 85°C

Also available in many other options.

- Actuators
- Bushings
- Terminations
- Vertical Mounting
- Horizontal mounting

NO. POLES	MODEL NO.	SWITCH FUNCTION			MOM. = Momentary	SCHEMATICS
		POS. 1	POS. 2	POS. 3		
SPDT	C&K7101SD1CBE	ON	NONE	ON		
	C&K7103SD1CBE	ON	OFF	ON		
	C&K7105SD1CBE	MOM.	OFF	MOM.		
	C&K7107SD1CBE	ON	OFF	MOM.		
	C&K7108SD1CBE	ON	NONE	MOM.		
DPDT	C&K7201SD1CBE	ON	NONE	ON		
	C&K7203SD1CBE	ON	OFF	ON		
	C&K7205SD1CBE	MOM.	OFF	MOM.		
	C&K7207SD1CBE	ON	OFF	MOM.		
	C&K7208SD1CBE	ON	NONE	MOM.		