# TEST EQUIPMENT

## SEMTRONICS P/L

## MULTIMETERS

### LOW COST DMM

DMM		QM1500	

- 12.5mm High Display LCD • Transistor Test
- Diode Test

• 3.5 Digit

- 10 Amp Current
- Plug-in Leads

This is a full feature meter with plug-in 4mm probes AND transistor tester. This is the ideal first multimeter, and will give years of faithful service, in fact, you will only need to replace this meter if you require a unit with very high input impedance.

### DATA ON HOLD DMM

#### QM1520

Specifications: DC Voltage:

Max input:

New Professional Look	Specifications: DC Voltage:
Transistor Test	0
•Diode Test	
•3.5 Digit	
•10A Current	DC Amps:
Low Battery Indication	•
•Spectacular Features For The Price	
Full feature digital multimeter with data hold. Now has	AC Volts:

Full feature digital multimeter with data hold. Now has a 12 month over the counter replacement warranty if the unit has a manufacturers fault. Includes 4mm banana sockets and quality high voltage test probes with nifty probe tip protectors.

**BACKLIT DMM** 

#### **OM1522**

•New Professional Look	
•Data Hold	
Continuity Buzzer	
Transistor / Diode Test	
•3.5 Digit	
•10A Current	
•Low Battery Indication	

Includes continuity buzzer, data hold and the LCD screen is backlit. Push the backlight button and you have 5 seconds before it turns off automatically. 12 month warranty. Includes high quality voltage test probes with nifty probe tip protectors.

### TEMPERATURE DMM

QM1525

- New Professional Look
- •Data Hold
- Contiuity Buzzer
- Transistor / Diode Test
- Includes Temperature Probe
- -20 to 1000°C •3.5 Digit
- •10A Current •Low Battery Indication

Another fantastic new DMM for 99. This DMM also includes a temperature probe. We have never been able to sell a temperature probe meter before for more than twice the cost of this unit. Includes 4mm banana type high voltage safety test probes and standard thermocouple type thermo test probe.

DC Amps:	200μA, 2000μA, 20mA, 200mA, 10A Overload protected ±2%	
AC Volts:	200V, 750V, max input 750V rms input imped. 1 Meg $\pm 1.2\%$	
Resistance:	200O, 2000O, 20K, 200K, 200KO ±1%	
Dimensions:	68 x 125 x 23mm.	
Specifications: DC Voltage:	200mV, 2V, 20V, 200V, 600V +/-0.5%. Overload protected 250V RMS for 200mV range. 600V DC RMS AC for other ranges	

200mV, 2000mV, 20V, 200V, 1000V

1000V DC $\pm$ 0.5%. Overload protected  $\pm$ 2%

Amps:	200µA, 2mA, 20mA, 200mA, 10A +/- 1% on most ranges. Overload protected (not 10A).	
Volts:	200V, 600V, +/-1.2%. Overload protect ed.	
	2000 200 200 2000 1000	

**Resistance:** 2000, 2KO, 20K, 200K, 1MO +/-0.8%. 138 x 69 x 31mm. **Dimensions:** Overload protected. Diode and transistor test.

Specifications: DC Voltage:	200mV, 2V, 20V, 200V, 600V +/- 0.5%. Overload protected 250V RMS for 200mV range. 600V DC RMS AC for other ranges.
DC Amps:	200µA, 2mA, 20mA, 200mA, 10A +/-1% on mostranges. Overload protected (not 10A).
AC Volts:	200V, 600V, +/-1.2%. Overload protected.
Resistance:	200O, 2KO, 20K, 200K, 2MO +/-0.8%.
Dimonsions	128 x 60 x 21mm

**Dimensions:** 138 x 69 x 31mm Overload protected. Diode and transistor test.







QM1520



**Specifications:** 

DC Voltage:	200mV, 2V, 20V, 200V, 600V ±0.5%. Overload protected 250V RMS for 200mV range. 600V DC RMS AC for other ranges	
		Part Number
DC Amps:	200µA, 2mA, 20mA, 200mA,	OM1525
_	$10A \pm 1\%$ on most ranges.	
	Overload protected (not 10A).	
AC Volts:	200V, 600V, ±1.2%.	
	Overload protected.	
Resistance:	200O, 2KO, 20K, 200K, 2MO	
	$\pm 0.8\%$ . Overload protected. Diode	
	and transistor test.	
Dimensions:	Size 138 x 69 x 31mm.	

