

## Rectifier diodes

If(av) Max A	VRRM						CASE	L	W	
	200V	300V	400V	600V	1000V	FAST				
1			FR104		FR107	Y	DO-41	PLASTIC	5.2	2.7
1	MUR120		1N4936 UF4004	1N4937	UF4007	Y	DO-41	PLASTIC	5.2	2.7
1			1N4004		1N4007		DO-41	PLASTIC	5.2	2.7
1	BYV26E (100V)						SOD-57	GLASS	4.6	3.8
1.5					BYV96E	Y	SOD-57	GLASS	4.6	3.8
1.5	BYW100-200						F-126	GLASS	6.35	3.05
1.7			BYD73G			Y	SOD-81	PLASTIC	5.2	2.7
2	BYV27-200						SOD-57	GLASS	4.6	3.8
3				MR856	FR307	Y	DO-210AD	PLASTIC	9.5	5.6
3					BYW96E	Y	SOD-64	GLASS	5	4.5
3			BYT03-400			Y	DO-27A	PLASTIC	9.8	5.1
3					1N5408		DO-201AD	PLASTIC	9.5	5.6
3					HER308		DO-201AD	PLASTIC	9.5	5.6
3			UF5404			Y	DO-210AP	PLASTIC	9.5	5.3
3.5	BYV28-200					Y	SOD-64	GLASS	5	4.5
4				MUR460	MUR4100E	Y	267-03	PLASTIC	9.39	6.35
6			6A4	MR756			DO-41	PLASTIC	5.2	2.7
6.5		BY249 300				Y	TO220			
7			BYV29-400	BY229 600	BY229 800 (800V)	Y	TO220			
8	BYW29-200		FR804			Y	TO220			
8	MUR820					Y	TO220			
8	BYW80-200A					Y	TO220x2			
10	BYV32-200					Y	TO220			
12					BYT12PI-1000	Y	TO220AC			
15				MUR1560		Y	TO220AC			
20	BYW51-200					Y	TO220			



## Stud mount diodes

A	600V	1200V	Stud thread	Style
22Amps	A2B-22-06	A2B-22-12	6mm	CATHODE - CASE
22Amps	A2A-22-06	A2A-22-12	6mm	ANODE - CASE
22Amps	A1B-22-06		10/32"	CATHODE - CASE
22Amps	A1A-22-06		10/32"	ANODE - CASE

