


## MAINS TRANSFORMERS

### 9V, 150MA, CENTRE TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 1.35VA  
 Insulation - Class E (120°C)  
 Magnetising current - <35mA  
 Temperature rise - <60°C  
 Regulation -  $\approx 8\%$   
 AC fuse - Internal  
 Weight -  $\approx 120g$

Approval Certificate No. CS/813/Q



Secondary Voltages Available:

4.5V 150mA  
 9V 150mA



Primary and secondary fitted with 200mm fly leads.

Part Number	A	D	L	W	H
M2840	48	39	38	16	32

### 12.6V, 150MA, CENTRE TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 1.89VA  
 Insulation - Class E (120°C)  
 Magnetising current - <30mA  
 Temperature rise - <65°C  
 Regulation -  $\approx 7.5\%$   
 AC fuse - Internal  
 Weight -  $\approx 180g$

Approval Certificate No. CS/813/Q



Secondary Voltages Available:

6.3V 150mA  
 12.6V 150mA



Primary and secondary fitted with 200mm fly leads.

Part Number	A	D	L	W	H
M2851	48	39	38	18	32

### 24V, 150MA, CENTRE TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 3.6VA  
 Insulation - Class E (120°C)  
 Magnetising current - <40mA  
 Temperature rise - <65°C  
 Regulation -  $\approx 12\%$   
 AC fuse - Internal  
 Weight -  $\approx 230g$

Approval Certificate No. CS/813/Q






Secondary Voltages Available:

12V 150mA  
 24V 150mA

Primary and secondary fitted with 200mm fly leads.

Part Number	A	D	L	W	H
M2854	54	46	43	22	36

## POWER IRAN




Type 1

Type 2

### 12.6V, 300MA, CENTRE TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 3.78VA  
 Insulation - Class E (120°C)  
 Magnetising current - <40mA  
 Temperature rise - <65°C  
 Regulation -  $\approx 12\%$   
 AC fuse - Internal  
 Weight -  $\approx 240g$

Approval Certificate No. CS/813/Q



Secondary Voltages Available:

6.3V 300mA  
 12V 300mA


Primary and secondary fitted with 200mm fly leads.

Part Number	A	D	L	W	H
M2852	54	46	43	22	36

### 12.6V, 500MA, CENTRE TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 6.3VA  
 Insulation - Class E (120°C)  
 Magnetising current - <45mA  
 Temperature rise - <65°C  
 Regulation -  $\approx 13\%$   
 Recommended AC fuse - 100mA  
 Weight -  $\approx 385g$

Approval Certificate No. CS/813/Q



Secondary Voltages Available:

6.3V 500mA  
 12.6V 500mA


Primary and secondary fitted with 200mm fly leads.

Part Number	A	D	L	W	H
M2853	60	38	50	20	45

### 30V, 150MA, CENTRE TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 4.5VA  
 Insulation - Class E (120°C)  
 Magnetising current - <45mA  
 Temperature rise - <65°C  
 Regulation -  $\approx 15\%$   
 AC fuse - Internal  
 Weight -  $\approx 240g$

Approval Certificate No. CS/813/Q



Secondary Voltages Available:

15V 150mA  
 30V 150mA


Primary and secondary fitted with 200mm fly leads.

Part Number	A	D	L	W	H
M2855	54	52	44	30	36

### 6.3V - 15V, 1A, MULTI-TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 15VA  
 Insulation - Class E (120°C)  
 Magnetising current - <60mA  
 Temperature rise - <60°C  
 Regulation -  $\approx 10\%$   
 Recommended AC fuse - 1A  
 Weight -  $\approx 555g$

Approval Certificate No. CS/813/Q



Secondary Voltages Available:

6.3V : 7.5V : 8.5V  
 9.5V : 12.5V : 15V  
 1 Amp



Primary fitted with 200mm fly leads  
 Secondary taps have solder tags

Part Number	A	D	L	W	H
M2155	71	54	60	27	51

### 15V - 30V, 1A, MULTI-TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 30VA  
 Insulation - Class E (120°C)  
 Magnetising current - <80mA  
 Temperature rise - <65°C  
 Regulation -  $\approx 8\%$   
 Recommended AC fuse - 500mA  
 Weight -  $\approx 1kg$

Approval Certificate No. CS/814/Q



Secondary Voltages Available:

15.0V : 17.5V : 20.0V  
 24.0V : 27.5V : 30.0V  
 1 Amp


Primary fitted with 200mm fly leads.  
 Secondary taps have solder tags.

Part Number	A	D	L	W	H
M6672	84	70	69	40	60

### 12V - 18V, 1A, MULTI-TAPPED

Primary Voltage - 240V AC  
 Total VA rating - 18VA  
 Insulation - Class E (120°C)  
 Magnetising current - <65mA  
 Temperature rise - <60°C  
 Regulation -  $\approx 10\%$   
 Recommended AC fuse - 250mA  
 Weight -  $\approx 650g$

Approval Certificate No. CS/813/Q



Secondary Voltages Available:

12V 1Amp  
 15V 1Amp  
 18V 1Amp

Primary fitted with 200mm fly leads.  
 Secondary taps have solder tags.

Part Number	A	D	L	W	H
M2154	71	62	60	33	51